


FLYTECH

Versatile all-in-one POS terminal

POS337N2



15.6" PCAP
touch screen



Intel® Elkhart Lake



Fanless system



Easy to swap M.2 SSD



Superior connectivity &
expandability



"Ready-made"
stand options

POS337N2



System	Motherboard	F34
	Processor	Intel® Elkhart Lake Celeron J6412
	Memory	1x DDR4 up to 16GB
	Storage	128GB SSD (M.2) up to 512G
Display	Size and Resolution	15.6" 1920x1080
	Touch Screen	True-Flat PCAP multi-touch
Expansion	M.2 (E Key)	1 (for expansion cards like Wi-Fi / BT)
	USB Type-A	2x USB3.0 2x USB2.0
	USB Type-C	1x USB2.0 (data only) 1x USB3.0 (data only)
	FeDP	1x Flytech proprietary miniDP (for 2nd display)
I/O ports	Serial Port	2x DB9 (default 0V; COM1/COM2: 0V, 5V, 12V)
	LAN	1x RJ45
	Cash Drawer	1x RJ11/RJ12
	DC Jack	1x 4PIN (with latch)
Optional I/O	Powered USB	1x Powered USB 12V1x Powered USB 24V
Audio	Internal Speaker	1x 3W (Option)
Indicator	Power Button	1
	Power LED	1
Power	Power Adapter	65W / 19V (120W/19V with PUSB 12V & 24V)
Communication	WLAN + BT	802.11 a/b/g/n/ac/ax Wi-Fi 6 series, BT4.0
Peripheral	2nd Display	15.6" 2nd Display with touch
Certificate	EMC & Safety	FCC Class A, CE Mark, LVD
Environment	Operating Temperature	0°C ~ 35°C (32°F ~ 95°F)
	Storage Temperature	-20°C ~ 60°C (-4°F ~ 140°F)
	Humidity	20% ~ 85% RH non-condensing
Dimensions	Dimensions (W x D x H)	369 x 230 x 310 mm (14.5" x 9.1" x 12.2")
Weight	Weight	6.5KG
Mounting	VESA Mount	100 x 100
OS Supported		Android 13, Windows 10 IoT Enterprise, Linux

※ PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE

China - Hong Kong SAR



Rm01, 6/F, Blk A, Tonic Industrial Centre, 26 Kai Cheung Road, Kowloon Bay, Kowloon, Hong Kong.



852-3525-5800



852-2751-7447



sales@flytech.com.hk

