
VFD-800

Reliable and Brighter

VFD800 have option for 2 interface, USB and RS232 (Serial). Both interface could support 5~12V power supply. This to prevent damage to the VFD by improper power input and the brightness of VFD800 is 1000cd/m2, It is 5 times bright than LCD customer display.



- Clear, Easy-To-Read VFD
 - ESC/POS command 100% compatible
 - OPOS/JPOS Driver
-

VFD800

General

Number of character	40 (20 columns x 2 lines)
Brightness	500~1000 cd/m2
Character	5 x 7 dot matrix
Character type	95 Alphanumeric, 32 International Characters
Character size	5.5 (H) x 9.2 (W) mm
Dot Size (X x Y)	0.86 x 1.2 mm
Download characters	9 characters
Panel Dimension	220 (W) x 50 (D) x 87 (H) mm
Pole Dimension	Per support length: 130 (L) x 34.5 (Dia) mm
Base Dimension	217 (W) x 106 (D) x 33 (H) mm
Viewing Angle	Max. 90 degrees
Horizontal Rotation	Max. 355 degrees
Weight	Approx. 980 grams

Commands Mode Language Support

UITIMATE, LD220, AEDEX, UTC/S, UTC/P, ADM788, DSP800, CD5220, EMAX, LOGIC CONTROLUS English, Int'l English, Bosnia, Croatian, Czech, Danish, Dutch, Estonian, Faroese, Finnish, Flemish, French, Fr Canadian,

German, Greek, Hebrew, Hungarian, Icelandic, Indonesian, Irish, Italian, Katakana, Latvian, Lithuanian, Norwegian, Polish, Portuguese, Romanian, Russian, Slovene, Slovak, Spanish, Swedish

Interface

RS-232 (Serial) / USB

[Notice] : Specification are subject to change without notice

For more information : www.code-soft.com

Code Soft International Information Co. Ltd.

Room 319, Block C, The NEW Generation Info Tech Park, Chuangye Road, No.139, Bao'An District, Shenzhen, P.R.China.