

TP-D825

Thermal Receipt Printer



- Integrated board, higher reliability, more durable
- Support GB18030 Font, multiple International Languages
- Rich communication interface intelligent voice prompt, simple operation
- Support network printing status monitoring, computer multi-connection printing
- Embedded web page, directly through the IE to configure the printer
- Support Android version 12

Physical Parameter	
Printing method	Direct thermal
Resolution	203 Dpi
Print Width	55-60 mm
Print Speed	250 mm/s
Character size	ANK Font, Font A : 12x24dots Font B : 9X17 mm (9×17 dots) Simplified/Traditional Chinese : 24x24dots
Font	Standard GB18030
Print Command	Compatible with ESC/POS emulation
Auto Cutter	Partial
Paper Roll	80 mm
Dot Density	576 dots/line; 512 dots/line
Paper roll	80m
Diameter of paper core	1.7cm
Interface	USB+Ethernet or USB+Ethernet+Bluetooth or USB+Ethernet+Bluetooth+Audio or USB+Ethernet+WiFI
Reliability	Printing head life: 150 km Auto cutter life: 1 million cuts
Barcode Type	UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) /CODABAR/ITF/CODE39/CODE93/CODE128 QR CODE
Paper Thickness	0.06~0.08mm
Input Buffer	800KB~1MB
NV Flash	256K Bytes
Adapter	outside
Adapter input	AC 110V/220V , 50Hz ~ 60Hz
Adapter output	DC 24/2.5A
Printer input	DC 24V/2.5A
Cashdrawer out	DC 24V/1A
Working environment	Temperature(0~45°C), humidity (10~80%)
Storage environment	Temperature(-10~60°C), humidity (10~90%)
Drivers	Win XP/Win Vista/Win 7/Win 8/Win 8.1/Win 10/Linux
Gross weight	1.78 kg
Dimensions	204 × 147 × 138mm (D × W × H)